

# MODEL NUMBER FXMQ96MFVJU, VRV INDOOR UNITS - FXMQ\_MF SERIES

## 100% outside air processing unit

Utilize a single VRV piping system to provide both comfort space conditioning and fresh air treatment from the FXMQ\_MFVJU series.

- Capacity range from 48 MBH to 96 MBH
- 100% outside air with discharge air temperature control
- Optional MERV 8 and MERV 13 filters



[Specifications](#) | [Dimensions](#) | [Application](#) | [Features](#) | [Benefits](#)

Specifications	
Family	FXMQ_MF
Model Type	Ducted
Cooling Capacity	96000 Btu/h
Heating Capacity	59000 Btu/h
Fan Air Flow Rate	1236 ft³/min
External Static Pressure	1.03 in
Sound Pressure Level	48 dBA
Minimum Circuit Ampacity	4.1 A
Maximum Overcurrent Protection	15 A 15
Frequency	60 Hz
Voltage	230 V

Weight	271 lb
--------	--------

## Dimensions

Depth	43-5/16 in
Width	54-3/8 in
Height	18-1/2 in
Pipe Connections - Liquid	3/8 in
Pipe Connections - Gas	7/8 in
Pipe Connections - Drain	PS1B (female thread)

## Application

- 100% Outside Air Conditioning

## Features

- Service access from below
- Greater design flexibility with a capacity range extended to 96 MBH
- Improved ductwork and filtration flexibility with high CFM and ESP capabilities of up to 0.96" W.G.
- 100 % OA capable with discharge air temperature control
- Optional MERV 8 and 13 filters
- Standard Limited Warranty: 10-year warranty on compressor and all parts

## Benefits

- Can connect to heat pump or heat recovery VRV

Air filter is not standard accessory, but please mount it in the duct system of the suction side. Select its dust collection efficiency (gravity method) 50 % or more.